



# **AUTHORISED REPAIRER STANDARDS**

## **GENERAL WORKSHOP EQUIPMENT**

## Authorised Repairer Standards - General Workshop Equipment

INDEX	Core Standard	Advanced Standard	Page
Vehicle Lift	•		3 <input type="checkbox"/>
Axle Stands	•		3 <input type="checkbox"/>
Universal Handling System	•		3 <input type="checkbox"/>
Bottle Jacks		•	3 <input type="checkbox"/>
Floor Jacks	•		4 <input type="checkbox"/>
Folding Crane	•		4 <input type="checkbox"/>
Hydraulic Press	•		4 <input type="checkbox"/>
Lifting chains	•		4 <input type="checkbox"/>
Four Wheel Alignment Equipment (PC based)	•		5 <input type="checkbox"/>
Tyre Changer		•	5 <input type="checkbox"/>
Wheel Balancer		•	5 <input type="checkbox"/>
Tyre Pressure Gauge	•		5 <input type="checkbox"/>
Tread Depth Gauge	•		6 <input type="checkbox"/>
Exhaust Gas Analyser		•	6 <input type="checkbox"/>
Diesel Smoke Meter	•		7 <input type="checkbox"/>
Air Conditioning / Refrigerant Management System	•		7 <input type="checkbox"/>
Charge/Recycle Station R12		•	7 <input type="checkbox"/>
A/C Flushing Kit		•	8 <input type="checkbox"/>
Digital Thermometer	•		8 <input type="checkbox"/>
UV Dye Injector Kit		•	8 <input type="checkbox"/>
Leak Detector Kit	•		8 <input type="checkbox"/>
UV Lamp	•		8 <input type="checkbox"/>
Oil Dispenser-Pneumatic	•		8 <input type="checkbox"/>
Oil Drain Equipment	•		9 <input type="checkbox"/>
Oil Filter Crusher		•	9 <input type="checkbox"/>
Air Compressor	•		9 <input type="checkbox"/>
Exhaust Extraction System	•		9 <input type="checkbox"/>
Parts Cleaner / Degreaser	•		10 <input type="checkbox"/>
Vacuum Cleaner	•		10 <input type="checkbox"/>
Water / Steam Pressure Cleaner	•		10 <input type="checkbox"/>
Workbench with Vice	•		11 <input type="checkbox"/>
Roller/Plate Brake Tester		•	11 <input type="checkbox"/>
Brake System Pressure Bleeder / Filler	•		11 <input type="checkbox"/>
Hydrometer		•	11 <input type="checkbox"/>
Cooling System Refiller	•		12 <input type="checkbox"/>
Headlamp Beam Setter	•		12 <input type="checkbox"/>
Battery Charger	•		12 <input type="checkbox"/>
Battery Tester	•		13 <input type="checkbox"/>
Vehicle Booster		•	13 <input type="checkbox"/>
Digital Multimeter	•		13 <input type="checkbox"/>
Hot Air Gun	•		13 <input type="checkbox"/>
Welding Equipment		•	14 <input type="checkbox"/>
Soldering Iron	•		14 <input type="checkbox"/>
Hot Air Gun	•		14 <input type="checkbox"/>
Fuel Retriever / Storage	•		14 <input type="checkbox"/>
Fuel Pressure Gauge Kit	•		14 <input type="checkbox"/>
Petrol Engine Compression Tester	•		15 <input type="checkbox"/>
Diesel Engine Compression Tester	•		15 <input type="checkbox"/>
Pressure/Vacuum Pump and Gauge Set	•		15 <input type="checkbox"/>
Cylinder Hone Equipment	•		15 <input type="checkbox"/>
Air Blow Gun	•		15 <input type="checkbox"/>
Endoscope		•	16 <input type="checkbox"/>
Windscreen Repair		•	16 <input type="checkbox"/>
Windscreen Remove/Refit		•	16 <input type="checkbox"/>
Air Drill	•		16 <input type="checkbox"/>
Electrical Drill	•		17 <input type="checkbox"/>
Bench Grinder		•	17 <input type="checkbox"/>
Riveting Tool	•		17 <input type="checkbox"/>
Cylinder Bore Gauge	•		17 <input type="checkbox"/>
Dial Indicator Gauge	•		18 <input type="checkbox"/>
Brake Disc/Drum Calipers	•		18 <input type="checkbox"/>
Torque Driver	•		18 <input type="checkbox"/>
Torque Wrenches	•		18 <input type="checkbox"/>
Vernier Gauge	•		19 <input type="checkbox"/>
Tachometer	•		19 <input type="checkbox"/>
Timing light	•		19 <input type="checkbox"/>
Inspection Lamps	•		19 <input type="checkbox"/>
Vehicle Protection Covers	•		<input type="checkbox"/>

## VEHICLE LIFT

Lifts with a minimum capacity of 3.0 t.  
Contact JEP for a full range of approved equipment



**Inground-Lift**  
Prices available on request  
**4-Post-Lift**  
Prices available on request  
**2-Post-Lift**  
Prices available on request

## AXLE STANDS NIKE HYDRAULICS

These stands with a capacity of 3.0 t are required each time a vehicle is lifted by a service jack. The safety of the operators working around and beneath the vehicle depends on the stands. These rugged and safe stands provide safe working conditions and incorporate a self-locking system for the ratchet bar.

- Heavy duty all welded steel construction
- Wide base area
- Top saddle and ratchet bar made in one piece



Order No. 311 1115 001 00  
Price available on request  
incl. freight

## UNIVERSAL HANDLING SYSTEM NIKE HYDRAULICS

The Universal Assembly Handling System with pneumatic and hydraulic lifting is designed to make the removal and replacement of major and subassemblies simpler and more efficient in service workshops and bodyshops. User convenience is increased as many jobs, where previously several technicians were required, can now be completed with just one technician. The system is delivered with a set of universal adaptors suitable for Jaguar cars and most other applications.



Order No. 311 3502 007 00  
Price available on request  
incl. freight

## BOTTLE JACKS NIKE HYDRAULICS

- Low manual pumping force facilitates use in uncomfortable positions
- Release valve permits safe, easy and precise control over rate of lowering
- Filter in oil reservoir protects against contamination

Lifting capacity 2 / 4 t  
Maximum height 400 / 445 mm



Order No. (2 t) 311 1115 004 00  
Price available on request  
Order No. (4 t) 311 1115 005 00  
Price available on request  
incl. freight

## FLOOR JACKS NIKE HYDRAULICS

Trolley jack suitable for vehicle servicing and repair. The rear swivel castors allow easy manoeuvrability and the wheels are made of glass fibre reinforced polyimide which give low rolling resistance, long life and help protect the modern workshop floor.

A detachable lifting pad protector is standard issue which helps to protect the vehicle bodywork and makes lifting safer by minimizing the risk of sliding. Capacity 2.0 t - max. height 527 mm - length 695 mm

Please contact JEP for more information on equipment that meets your local requirements.



Order No. **311 1114 001 00**  
 Price **available on request**  
incl. freight

## FOLDING CRANE CAM

A comprehensive range of robust and reliable workshop cranes to suit all needs. All models either fold down or have removable legs so that they require the minimum of storage. Each crane has been tested to a 25% overload capacity and comes with its own test certificate.

- Top quality hydraulics
- Hard wearing nylon wheels
- Safety overload valve
- Heavy duty swivel hook with safety latch

FC500, Lifting capacity 500 kg (298 1112 002 00)

FC750, Lifting capacity 750 kg (298 1112 003 00)



Order No. **298 1112 002 00**  
 Price **available on request**  
 Order No. **298 1112 003 00**  
 Price **available on request**  
excl. freight

## HYDRAULIC PRESS CAM

These presses are simple to operate with very reliable hydraulic pump and hydraulic cylinders. Constructed to give many years of trouble free operation, with precision machined components from high quality material. The hydraulic seals are manufactured from top quality materials using the latest technology.

C15H, 15 t (298 1113 001 00)

C20H, 20 t (298 1113 002 00)



Order No. **298 1113 001 00**  
 Price **available on request**  
 Order No. **298 1113 002 00**  
 Price **available on request**  
excl. freight

## LIFTING CHAINS NIKE

Thanks to the design of the hook, the chain can form a sling of any size without reduction of the safe working load. Safe working load: 5 ton/10 ton, Length: 1.6 m/2.0 m

TOK408, 5 t (311 0101 002 00)

TOK107, 10 t (311 0101 003 00)



Order No. **311 0101 002 00**  
 Price **available on request**  
 Order No. **311 0101 003 00**  
 Price **available on request**  
incl. freight

## FOUR WHEEL ALIGNMENT EQUIPMENT (PC BASED)

PC Based Alignment Equipment.

- 8 sensor heads
- CCD measuring technology
- Quick fit rim clamps
- Calibration kit
- In-rack wiring kit

Contact JEP for a full range of approved equipment.



Prices available on request

## TYRE CHANGER JOHN BEAN

Tyre Changer with an 10 - 24" wheel diameter capacity.

- Self-centering four-jaw chuck with two clamping cylinders
- 2-speed operation for the chuck by pedal operation
- Inner jaws equipped with plastic protectors for the rim



### Tyre Changer

Order No. 271 2101 007 00  
Price available on request

### Alloy Mate

Order No. 271 2101 002 01  
Price available on request

incl. freight

## WHEEL BALANCER JOHN BEAN

Wheel Balancer with an 10 - 24" wheel diameter capacity.

- Semi-automatic distance/offset entry
- Input of diameter and width through  $\pm$  buttons
- Dual digital display
- Data storage of up to 4 different wheels



Order No. 271 2102 009 00  
Price available on request

incl. freight

## TYRE PRESSURE GAUGE PCL

Autoportair with 0.76 m (30") hose, fitted with twin hold-on connector (open end) Calibration 0 - 10 bar and 0 - 140 lbf/in<sup>2</sup>, 6 litre

- Re-charges automatically when returned to charging point
- Inflation and deflation lever operation
- Tamper proof, master gauge, toughened glass
- Manufactured to EC Standards
- EC approved dial to 86/217/EC (bar scale only)
- EC approved pressure vessel to 87/404/EC
- Complies with BSEN 12645:1999
- Dimensions 300 x 600 x 200 mm, weight 49kg



Order No. 284 2104 001 00  
Price available on request

incl. freight

## TREAD DEPTH GAUGE MITUTOYO

The Tyre Tread Depth Gauge is designed specifically for automotive applications and incorporates the very latest in digital technology (patents held) with clear precise readings in increments of 0.01 mm over a 28 mm range. Suitable for tread depth, brake shoe and pad wear, the gauge offers excellent versatility in workshop and field use.

Mechanical Gauge [435 1160 001 00]

Measurement of tyre tread depth from 1-30 mm, vernier 1/10 mm



Order No. **435 1160 001 00**  
 Price **available on request**  
 Order No. **444 1160 002 00**  
 Price **available on request**  
incl. freight

## EXHAUST GAS ANALYSER SUN DIAGNOSTICS

The Gas Analyzer is a modular concept allowing a variety of products to connect to a central workstation.

Diagnostic Gas Analyser which features a unique graphical user interface, fast gas bench and ease of use. MOT approved.



Order No. **025 3103 024 00**  
 Price **available on request**  
incl. freight

## EXHAUST GAS ANALYSER KANE

Weighing just 1 kg, the handset fits comfortably in the hand and can run for up to 4 hours on its internal re-chargeable battery. Ideal for emission diagnostics, tuning, pre-compliance testing and for regulated testing where OIML R99 class 1 standards are specified. The programmed re-calibration procedure permits low cost servicing either on site or at approved European service facilities. The O2 and NO sensors are warranted for 2 years from date of purchase. The software includes pre-programmed language options, pre-programmed emission test, auto store & data logging, upgradeable analyser firmware and service software. Each kit is supplied in a hard carry case and includes the handset with water trap in a protective rubber sleeve; battery charger; 12 V adapter cable; high temperature probe; spare filters; RPM clamp; oil temperature probe; and multi-language software.

Auto 5-2, Five Gas Analyser Kit - Standard [525 3103 003 00]

Auto 4-2, Four Gas Analyser Kit - Standard [525 3103 004 00]



Order No. **525 3103 003 00**  
 Price **available on request**  
 Order No. **525 3103 004 00**  
 Price **available on request**  
incl. freight

## EXHAUST GAS ANALYSER TECNOTEST

Stargas working both as measuring unit and multi-function work station without connection to a PC. The central unit easily switches between exhaust gas analyser, Autodiagnosis, oscilloscope and diesel smokemeter. Stargas has an "open" instrument design allowing easy adaptation to possible future changes in regulations. The instrument is equipped with a large 256-color display, and can easily connect to a standard VGA monitor [incl.] or colour TV. Stargas can also be remotely controlled through an optional Infra red alphanumeric keyboard. Compact, lightweight and built-in 12 V battery power supply allow for portable and road test operation.



Order No. **266 3103 002 00**  
 Price **available on request**  
incl. freight



## DIESEL SMOKE METER

The Jaguar Equipment Programme offers a wide range of high quality Diesel Smoke Meters, designed and built by manufacturers with many years of experience. Each Smoke meter and accessory available through JEP is fully approved by Jaguar and is supplied with the highest levels of back-up, service and support.

Please contact JEP for more information on equipment that meets your local requirements.



Prices available on request

## AIR CONDITIONING / REFRIGERANT MANAGEMENT SYSTEM SUN DIAGNOSTICS

The unit is a single pass, fully automatic R134a Refrigerant Management System. The easy to use control panel guides the operator through a step-by-step programme to carry out a fully automatic recovery, vacuum, recycle and recharge sequence or any of these functions separately. The unit also features an integrated printer and dual integrated diagnostic temperature probes.



Order No. 025 4406 008 00  
Price available on request

## AIR CONDITIONING / REFRIGERANT MANAGEMENT SYSTEM ROBINAIR

This R134a-Refrigerant Management System offers an advanced level of automation and maximum flexibility for the operator. The machine has two primary operating modes, "manual" or "automatic" and rapidly recovers, recycles, evacuates and re-charges. Printer is included. Package prices also available.



Order No. 266 4406 014 00  
Price available on request  
incl. freight

## CHARGE/RECYCLE STATION R12 ROBINAIR

All of these portable multi refrigerant recovery units feature heavy duty oil-less compressors for fast efficient recovery. Simple operation through high visibility gauges and clear controls.

Safe and economical - high pressure cut out switches and engineering advances to keep cost down and quality up. Models include liquid and vapour recovery. Efficient heat exchange and cooling to allow efficient recovery in warm ambient temperatures. Available for medium (459 4409 009 00) or for medium and high pressure refrigerants (459 4409 008 00)



Order No. 459 4406 008 00  
Price available on request  
Order No. 459 4406 009 00  
Price available on request  
incl. freight

## A/C FLUSHING KIT ROBINAIR

Jaguar specific flushing kit for liquid refrigerant flushing of contaminated A/C systems. For use when replacing components or converting systems. This kit contains all the necessary bridges and adapters to enable open circuit high pressure flushing. Robinair machines utilise liquid refrigerant flushing to remove old / excess oil, contamination and internal debris. Effective flushing is essential when replacing components (especially compressors) that are being changed due to internal failure. The adapter kit enables your Robinair RMS unit to be converted to accept liquid refrigerant flushing. For use with refrigerant management stations AC 350, AC 500, 2404-048/47/46. Including all fittings for Jaguar cars.



Order No. **459 4406 001 07**  
 Price **available on request**  
incl. freight

## LEAK DETECTOR KIT ROBINAIR

UV leak detector kit for air conditioning and refrigeration systems. Includes UV lamp, UV detection glasses, A/C dye injector, dye cleaner, A/C hose assembly, fluorescent dyes, R-12 adapter. Including special Jaguar adaptors.



Order No. **459 4406 001 08**  
 Price **available on request**  
incl. freight

## DIGITAL THERMOMETER ROBINAIR

Hand held thermometer offers the accuracy, flexibility and ease of use coupled with the reliability that is required by industry today. Easy to read LCD digital display with a precise readout of temperature. Includes max./min. and hold button.

Temperature:  $-50^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$  ( $-58^{\circ}\text{F}$  to  $+302^{\circ}\text{F}$ )  
 Accuracy:  $\pm 0.5^{\circ}\text{C}$   
 Sampling Time: 500 msec



Order No. **266 4409 001 00**  
 Price **available on request**  
incl. freight

## UV LAMP ROBINAIR

Spot lamp with pistol grip. Inspection range 1.5 m (5 ft).  
 Bulb rating 50 W.  
 Lamp head 6 x 4.5 cm.  
 Cord length 4.3 m (14 ft).



Order No. **459 4406 001 04**  
 Price **available on request**  
incl. freight

## OIL DISPENSER-PNEUMATIC SAMOA

The 3:1 oil pump kit is a medium pressure air operated pump and is available for high or medium volume flow transfer of high viscosity lubricants and oil distribution through pipework, hose reels and meters.

- Pump may be mounted on mobile units, drums, tanks or walls
- Comprehensive kits include adaptors, air and oil hoses, isolator valves, air filter/regulators with gauges, mounting brackets and suction tubes where required
- Adjustable bung adapter



Order No. **421 6102 002 00**  
 Price **available on request**  
incl. freight



## OIL DRAIN EQUIPMENT SAMOA

Ideal for use under vehicle lifts and in pits. The oil is collected via a telescopic anti splash bowl and emptied by one of the following methods: wall mounted air operated suction discharge pump, integral air pump and quick release hose or by low air pressure discharge.

- Large capacity anti splash bowl with mesh filter
- Easy manoeuvrability with 2 fixed and 2 swivel wheels
- Level gauge
- Low pressure version comes complete with preset pressure regulator and safety valve. (not suitable for use with self-sealing outlet connections)
- Available with integral air pump (421 6105 015 00) or air pressure discharge (421 6105 016 00)



Order No. **421 6105 015 00**  
 Price **available on request**  
 Order No. **421 6105 016 00**  
 Price **available on request**  
 incl. freight

## OIL FILTER CRUSHER NIKE HYDRAULICS

Compact in size this Oil Filter Crushing Press is suitable for all sizes of workshop. The press can be mounted directly on to a 205-litre waste oil drum. The crusher has a powerful 11 tonne capacity that reduces filters to 20-25 % of their original size and removes 95% of oil from the filter. The pneumatically operated hydraulic pump means that there is no manual effort involved in the process and it works off normal workshop air supply.

- Reduces waste volume and disposal costs
- Suitable for filters up to 305 mm high by 130 mm diameter
- The collector can be used as a conventional waste oil trap
- Also suitable for crushing diesel fuel filters



Order No. **311 6108 001 00**  
 Price **available on request**  
 excl. freight

## AIR COMPRESSOR ATLAS COPCO

Atlas Copco's range of piston and screw compressors together with ancillaries provide quality air for all applications. Choosing the ideal compressed air system involves careful consideration of factors such as location, output requirements, working pressure, air quality and energy efficiency.

Please contact JEP regarding a compressor to meet your local requirements.



Prices **available on request**

## EXHAUST EXTRACTION SYSTEM PLYMOVENT/AES

Tailor-made extraction solutions for workshops of any size. A workshop analysis and a modular system make it possible to install the best new system or to modify an existing installation. MOT compliance guaranteed.

Please contact JEP for more information on equipment that meets your local requirements.



Prices **available on request**

## PARTS CLEANER / DEGREASER <sup>CHECO</sup>

Air operated models: Simple, versatile parts washer cleaners with unique patented operating system. There are no moving parts making these machines ultra-reliable. Cleaning solutions: Checo offer a full range of 100 litre quick change drums of long life solvents. The most popular choice is a safe high flash point solvent which does not require local exhaust ventilation and is of low odour.

Bath size 760 (30") x 510 (20") x 200 mm (8")

Also available in 110 V and 230 V all-electric operation.



Order No. **400 1130 001 00**  
 Price **available on request**  
incl. freight

## PARTS CLEANER / DEGREASER <sup>NILFISK</sup>

Special purpose low pressure cleaner, designed for the cleaning of brakes, machinery, engines, components, etc. The cleaning chemical solution is heated to 95°C by connecting the machine to a single phase electrical supply. The solution is then compressed to 6 bar, by means of workshop compressed air, before use.

- Fully mobile
- Tank Capacity: 18 litres
- Non solvent cleaning fluid
- Fast payback compared with rental



Order No. **208 1130 002 00**  
 Price **available on request**  
incl. freight

## VACUUM CLEANER <sup>NILFISK</sup>

The unit is easy to handle by one person and has a 46 litre bag system which is easy and hygienic to change. The standard motors give the machine an extremely long life span, reducing servicing and maintenance costs to a minimum. Use the machine to clean your machinery and equipment, your floor or, with attachment, your shelves.

- 2 x 1200 W motors
- Easy to handle by one person
- Large dust bag with 46 litres capacity
- Dust bag easy and hygienic to change



Order No. **208 6203 002 00**  
 Price **available on request**  
incl. freight

## WATER / STEAM PRESSURE CLEANER <sup>KÄRCHER</sup>

Mobile hot water steam pressure washer  
 Water flow rate: 280-530 l/h  
 Pump pressure: 30-120 bar  
 Max. temperature (feed 12°C): 140/80°C  
 Connected load: 3.0 kW  
 Fuel tank: 16 l  
 Detergent tank: 8 l



Order No. **007 6202 017 00**  
 Price **available on request**  
incl. freight

## WORKBENCH <sup>DURA</sup>

Heavy-duty workbench as part of the Dura Fitted Workshop™ co-ordinated range. Dimensions: H 950mm, W 1200mm, D 600mm.

Includes:

- Stainless steel worktop
- Lower shelf
- 4" Record No. 3 vice
- 3 mm steel vice mounting plate
- Requires assembly




Order No. **474 1116 003 00**  
 Price **available on request**  
excl. freight

## ROLLER/PLATE BRAKE TESTER

Platform-type or roller brake tester for vehicles up to 6.5 metric tons gross weight.

Please contact JEP for more information on equipment that meets your local requirements.



Price **available on request**

## BRAKE SYSTEM PRESSURE BLEEDER / FILLER <sup>ALBA</sup>

The brake bleeder has been designed to make the replacement of brake fluid a quick and simple task that can be completed by a single operator. The bleeder is connected to the vehicle battery or an alternative 12 V supply. The brake system is then pressurised via the fluid reservoir using the appropriate adapter cap. The motor will cut in and out as the system is bled, maintaining the fluid level and pressure automatically.



Order No. **314 2209 002 00**  
 Price **available on request**  
incl. freight

## HYDROMETER <sup>LEITENBERGER</sup>

Workshop tester for checking the concentration of antifreeze (scala A) in coolant or windscreen washer fluid (scale B).

A LIGHT/DARK dividing line (4) on different scales indicates the temperature in °C (optional in °F), down to which the fluid is protected against freezing. The specific gravity of the electrolyte in the battery is indicated in kg per l (scale C).

Adjustable eyepiece permits adaption to the user's eyesight. Supplied complete with pipette in a cardboard box.



Order No. **511 3302 001 00**  
 Price **available on request**  
incl. freight

**COOLING SYSTEM TEST KIT** LEITENBERGER

Delivery includes:

- Plastic adaptors
  - Pump TVU139/1
  - Hose FZ100K
  - Cooling system adaptors K60, K31, K61
  - Cap test adaptors DS60, DS31, DS61 in plastic case.
- Complete with tee piece.



Order No. **511 3301 007 00**  
 Price **available on request**  
 incl. freight

**VACUUM COOLING SYSTEM FILLER** LEITENBERGER

A vacuum is generated in the cooling system by means of the workshop compressed air supply (6-14 bar) and a venturi nozzle. Provided the vacuum remains constant, the cooling system can be rapidly filled, devoid of any air pockets, the coolant is drawn in under vacuum.

Delivery includes:

- 1 vacuum cooling system filler
- 1 venturi nozzle connectable
- 2 hoses (PVC) á 1.50 m

Supplied in a robust plastic case.



Order No. **511 3301 001 00**  
 Price **available on request**  
 incl. freight

**HEADLAMP BEAM SETTER** JOHN BEAN

This equipment is essential for quick and precise inspection and adjustment of vehicle headlamps. A power supply is not required and alignment is achieved quickly with a single mirror. The setter has a MOT approved measuring screen and is rail mounted.



Order No. **271 4301 001 00**  
 Price **available on request**  
 incl. freight

**BATTERY CHARGER** TRACTION CHARGER

This unit charges effectively Lead/Antimony, Lead/Calcium and Silver/Calcium batteries. Once connected to the battery, the battery charger detects the state of battery charge and then applies the appropriate charge rate and duration. When the battery is fully charged, the battery charger switches to 'standby', keeping the battery in a fully charged state and preventing excessive gassing and overcharging. This battery charger also incorporates a software program that has the capability to assist in the recovery of deeply discharged (sulfated) batteries. 10A



Order No. **345 4201 010 00**  
 Price **available on request**  
 incl. freight

## BATTERY TESTER MIDTRONICS

All 12 V batteries can be tested with the Micro 390 before or after charging. The battery's state of charge and condition can be quickly determined as well as if a bad cell caused failure. The tester has been programmed with a test algorithm especially for Jaguar batteries and after the test is complete, it will display a test code required for the Jaguar Battery Care Program. At low temperatures, the test can be run with temperature compensation for greater accuracy. A LCD display shows the battery's voltage, state of charge and the diagnosis. The tester is protected against reverse polarity connection and electrical or computer-generated noise from the engine or charging system.



Order No. **063 4203 001 00**  
 Price **available on request**  
incl. freight

## VEHICLE BOOSTER DMS

The user can use this for many starts between charging or frequent starting including heavy diesels. Suggested for all 12 V vehicles including heavy diesels.

MB700: 383 4202 005 00

700 cold cranking amps.; 16 A/h, 9.2 kg, 2 A charger; 1.4 m, 25 mm<sup>2</sup> cable

MB800: 383 4202 007 00

800 cold cranking amps.; 36 A/h, 18 kg, 4 A charger; 1.8 m, 50 mm<sup>2</sup> cable



Order No. **383 4202 005 00**  
 Price **available on request**  
 Order No. **383 4202 007 00**  
 Price **available on request**  
incl. freight

## DIGITAL MULTIMETER PEAKTECH

New construction product with a high-performanced housing, which is secured against shocks. The overvoltage CAT III/1000V, overload- and transient protection, input warning beeper, auto-polarity operation, are some of the important features of this model.

- 3 1/2 digit, 18 mm LCD display; max. 1999
- Auto power off
- Diode test, continuity test, MAX/DATA hold function
- Safety: IEC-1010-1; CAT III 1000 V
- Delivery includes: Battery, safety test leads, manual



Order No. **501 4102 002 00**  
 Price **available on request**  
incl. freight

## HOT AIR GUN ALBA

Two speed/two temperature hot air gun, suitable for heat shrinking of electrical insulators. Supplied with heat deflector.

220-240 V

750 W/1500 W

300°C/500°C



Order No. **314 4503 001 00**  
 Price **available on request**  
incl. freight

## WELDING EQUIPMENT

Please contact JEP for information on equipment that meets your local requirements.



Prices available on request  
incl. freight

## LARGE SOLDERING IRON

Class 1 electrically insulated soldering irons with cool grip handle which stays comfortable during prolonged use. Fitted with replaceable soldering tip.

Includes 1.5 m of cable with BS approved 230 V/13A plug.

290 1168 006 00 - 100 W

290 1168 007 00 - 30 W/230 V



Order No. 290 1168 006 00  
Price available on request  
Order No. 290 1168 007 00  
Price available on request  
excl. freight

## FUEL RETRIEVER / STORAGE WALLMEK

The fuel retriever is designed specifically for the safe removal and storage of petrol and diesel fuel. This is achieved by passing a tube down the filler neck. In some cases this is not possible therefore adaptors are available to remove the fuel directly through the fuel lines. The unit simple attaches to the workshop airline, this creates a vacuum in the container and the fuel is sucked into the pressure vessel. Once the repair to the vehicle is completed, simple reverse the controls and the fuel is then replaced into the tank.



Order No. 522 3202 001 00  
Price available on request  
incl. freight

## FUEL PRESSURE GAUGE KIT LEITENBERGER

System pressure tester for mechanical and electronic fuel injection systems. An adjustable three-way-valve located between the warm-up regulator and fuel distributor permits the system pressure and control pressure to be tested, and the fuel injection system to be checked for leakages. High quality gauge with robust protective rubber cap and hook, DS 100 mm (4"), 0-10 bar/0-140 psi, graduation 0.10 bar. 3-way valve assembly, 3 hoses each end with coupling and adapters. Supplied in robust plastic case.



Order No. 511 3216 001 00  
Price available on request  
incl. freight



## PETROL ENGINE COMPRESSION TESTER SYKES PICKAVANT

The tester is easy to use and is supplied with adaptors and thread chasers for a range of engines. A clear, easy to read gauge provides accurate readings and a pressure relief valve maintains the reading until the valve is released. This also enables multiple tests to be carried out on the same cylinder without removing the tester. Brass fittings and a rubber-shrouded gauge add to the durability of the product. The gauge and accessories are supplied in a custom-made storage case.



Order No. **276 3107 001 00**  
 Price **available on request**  
incl. freight

## DIESEL ENGINE COMPRESSION TESTER SYKES PICKAVANT

The tester is easy to use on both direct and indirect systems and is supplied with adaptors and a flexible hose to allow access to awkward areas. A clear, easy-to-read gauge provides accurate readings and a pressure relief valve maintains the reading until the valve is released. This also enables multiple tests to be carried out on the same cylinder without removing the tester. Quick coupling adaptors, brass fittings and a rubber-shrouded gauge add to the appearance and durability of the product. The gauge and accessories are supplied in a custom-made storage case.



Order No. **276 3113 001 00**  
 Price **available on request**  
incl. freight

## PRESSURE/VACUUM PUMP AND GAUGE SET ALBA

This test kit combines both vacuum and pressure capabilities for general use.



Order No. **314 3108 001 00**  
 Price **available on request**  
incl. freight

## CYLINDER HONE EQUIPMENT SEALEY

Four cylinder-honing tools in one set covering 18 mm to 89 mm cylinder bores.

Suitable for honing and de-glazing car brake and clutch cylinders plus engine cylinders. Adjustable honing pressure and flexible drive shaft.



Order No. **290 1168 008 00**  
 Price **available on request**  
excl. freight

## AIR BLOW GUN ALBA

This equipment is recommended for use on all Diesel engines prior to service and repair work on fuel system components. The gun comes with a crevice nozzle, a collection bag and a flexible hose, for highly effective cleaning around the fuel injector, fuel pump and supply lines as specified in Diesel engine workshop manual operations.

- Enables effective cleaning around fuel injectors, fuel pump and the high pressure fuel supply line
- One handed operation
- Converts from vacuum gun to blow gun



Order No. **314 6208 001 00**  
 Price **available on request**  
incl. freight

## ENDOSCOPE <sup>ALBA</sup>

Based on new fibre optic technology, this unit, fitted with a wide-angle lens and high intensity bulb, enables internal inspection of parts of the engine, transmission components, bodywork etc. without the need for disassembly. The cable is flexible and stays in a fixed position until adjusted and the endoscope is able to fit into areas as small as 11 mm or 6 mm.

Length 450 mm (900 mm length also available). Supplied with high intensity bulb (with spare) and mirror pack as standard.

Endoscope 6 mm (314 3111 005 00)

Endoscope 11 mm (314 3111 001 00)



Order No. **314 3111 005 00**  
Price **available on request**

Order No. **314 3111 001 00**  
Price **available on request**  
incl. freight

## WINDSCREEN REPAIR <sup>ESPRIT</sup>

The Professional Repair System (261 5125 004 00) will repair star breaks, bulls eyes and crack damage on any laminated windscreen. It is designed for the workshop that demands the best with no compromise and is in 220/240 V for ultimate power and performance.

The Compact System (261 5125 003 00) is designed for the workshop that demands the best quality but at a budget price. Based on the Esprit Professional system but in 12 V with the Esprit Auto bridge.



Order No. **261 5125 003 00**  
Price **available on request**

Order No. **261 5125 004 00**  
Price **available on request**  
incl. freight

## WINDSCREEN REMOVE/REFIT <sup>BTB</sup>

An air powered system for the safe removal of bonded glass from vehicles, without damaging the glass, encapsulation, pinch weld or mouldings. The system will also remove body protection mouldings, emblems, spoilers and badges, without damaging painted panels.



Order No. **300 5122 007 00**  
Price **available on request**

incl. freight

## AIR DRILL <sup>SERVIS AIR</sup>

These air drills are available with 1/2" and 3/8" chuck, in the standard pistol design, or with 3/8" chuck and compact straight design. The two pistol drills have reversible motors and are lightweight aluminium construction.

SA-865, 1/2", capacity reversible 800 rpm (286 5404 001 00)

SA-863, 3/8", capacity reversible 1800 rpm (286 5404 002 00)



Order No. **286 5404 001 00**  
Price **available on request**

Order No. **286 5404 002 00**  
Price **available on request**  
excl. freight

## ELECTRICAL DRILL <sup>SEALEY</sup>

Cordless Hammer Drill/Driver Extra Super Torque 18 V 1Hr charge.  
 Extra powerful fan-cooled motor develops up to 310 Nm torque.  
 Hammer action. Gearbox with 2 mechanical speed ranges.  
 Variable speed, reverse and power brake. 1 hour charge.  
 13mm keyless chuck. 1450 rpm maximum speed.  
 12 position torque control allowing 24 different torque settings over the  
 2 speed ranges.  
 Incl. battery (290 1168 009 00)  
 Excl. battery (290 1168 005 00)



Order No. **290 1168 009 00**  
 Price **available on request**  
 Order No. **290 1168 005 00**  
 Price **available on request**  
 incl. freight

## BENCH GRINDER <sup>SEALEY</sup>

Ready to use. Supplied with one coarse and one wire wheel.  
 Complete with eye shields.  
 BG150 XLW/98 - Bench Grinder 6" 375 W/230 V c/w  
 Wire Wheel 375 W/230 V, 3000 rpm.



Order No. **290 1168 001 00**  
 Price **available on request**  
 incl. freight

## RIVETING TOOL <sup>SEALEY</sup>

Hand Riveter - Aluminium  
 GS/TUV approved drop forged aluminium body. Heavy duty SCM4 grade  
 jaws. PVC handle grips. Supplied with four nozzles to accept 2.4 mm(3/32"),  
 3.2 mm(1/8"), 4.0 mm(5/32") and 4.8 mm(3/16") rivets and nozzle spanner.



Order No. **290 1168 002 00**  
 Price **available on request**  
 incl. freight

## CYLINDER BORE GAUGE <sup>MITUTOYO</sup>

Of rugged construction this workshop instrument is perfect for accurate  
 measurement of bore diameters in the range 50-150 mm. Taper, bell mouth  
 and out of round conditions are easily revealed by this precision gauge.  
 Eleven interchangeable anvils are supplied to cover the range, all with  
 polished tungsten carbide contact points for long life and finished to a large  
 radius for close-tolerance repeatability. The clear, easy-to-read dial  
 indicator (graduated to 0.01 mm) is supplied complete with adjustable  
 tolerance markers and an impact-resistant protective shroud.



Order No. **444 3118 001 00**  
 Price **available on request**  
 excl. freight

## DIAL INDICATOR GAUGE <sup>SEALEY</sup>

Precision mechanism with 55 mm dial and locking rotating bezel. Interchangeable foot.

0 - 100 1/2" Travel Imperial or 0 - 100 10 mm Travel Metric.

Imperial (290 1168 003 00)

Metric (290 1168 004 00)



Order No. **290 1168 003 00**  
Price **available on request**

Order No. **290 1168 004 00**  
Price **available on request**


excl. freight

## BRAKE DISC/DRUM CALIPERS <sup>MITUTOYO</sup>

These high quality, easy to use, stainless steel digital-reading calipers are specifically designed for measuring disc and drum brake components to a resolution of 0.01 mm. The jaws are specially shaped for saving time when checking drum diameters, pad and disk wear and making shoe setting measurements. Digital clarity from large LCD displays together with simple 'set and forget' origin (zero) setting and offset reading capabilities make conventional tools obsolete. Both models run 20,000 hrs on a single-cell battery.

Drum Caliper - Range: 0-300 mm (444 1153 001 00)

Disc Caliper - Range: 0-150 mm (444 1153 002 00)



Order No. **444 1153 001 00**  
Price **available on request**

Order No. **444 1153 002 00**  
Price **available on request**

incl. freight

## TORQUE DRIVER (0-4.0 NM) <sup>BAHCO BELZER</sup>

Torque screwdriver 6976CN with scale and adjustment ring. 1/4" - male square.

Finish: shank nickel and chrome-plated, handle anodised, colour black.

- Smooth disengagement prevents overtightening
- Accurate and easy setting guarantees accordance with the requirements of DIN/ISO 6789/EN26789/1994
- Bi-directional operation with torque limiting effect
- Automatic re-setting by precision radial ball clutch
- Comprehensive range of accessories for universal applications
- Accuracy  $\pm 5\%$

With additional female square to hold a sliding T-handle.



Order No. **510 1168 001 00**  
Price **available on request**

incl. freight

## TORQUE WRENCHES (RANGE 3-500 NM) <sup>BAHCO BELZER</sup>

Torque wrenches with scale. Window Clicker Wrench.

Finish: Chrome plated.

- Easy to read "Window" scale.
- Accuracy:  $\pm 3\%$ , single direction
- A pull down locking knob on a grip for quick and easy torque adjustment
- Single torque scale for easy use
- Fixed ratchet head, 32 teeth, 11.25° action
- Locking mechanism keeps the socket captive
- Quick change of sockets by pressing the release button
- Handle customised to give optimum user comfort and with a 0.1 Nm graduation

7451-20: 3/8", 2-20 Nm (510 1128 001 00)

7851-200: 1/2", 20-200 Nm (510 1128 002 00)

7851-340: 1/2", 70-340 Nm (510 1128 003 00)



Order No. **510 1128 001 00**  
Price **available on request**

Order No. **510 1128 002 00**  
Price **available on request**

Order No. **510 1128 003 00**  
Price **available on request**

excl. freight

## TORQUE WRENCH 150-700 NM, 3/4" SYKES PICKAVANT

- Ratchet head
- 150 - 700 Nm
- 3/4" square drive
- Calibration certificate



Order No. 276 1128 001 00  
 Price £ 252.00  
 incl. freight

## VERNIER GAUGE SEALEY

Vernier Calliper 6"/150 mm (0.01 mm - 1/1000" Acc). High quality, hardened and tempered stainless steel calliper. Dual locking carriage with micro-thumb adjustment. Metric and Imperial scales graduated in 0.01 mm and 0.001".



Order No. 290 1153 003 00  
 Price £ 18.90  
 incl. freight

## TACHOMETER CRYPTON

This high performance, easy to use Laser Tachometer reads RPM by a simple 'on target' indication using the reflective tape supplied. The unit has an operating range of up to 1 metre and an Accuracy of ±1 rpm. It is battery operated (supplied with 4 x 1.5 V AA Alkaline Batteries) and is supplied in a protective case with comprehensive multi-lingual instructions.



Order No. 026 3106 001 00  
 Price £ 170.00  
 incl. freight

## TIMING LIGHT CRYPTON

- Digital readout of advance, RPM, Dwell and Volts
- Heavy duty timing light, with a rubber nose protector
- Clip-on HT inductive pickup
- Detachable replaceable leads
- Suitable for all types of ignition systems with any number of cylinder

Petrol (026 3105 003 00)

Petrol + Diesel (026 3105 002 00)



Order No. 026 3105 002 00  
 Price £ 237.00  
 Order No. 026 3105 003 00  
 Price £ 89.00  
 incl. freight

## INSPECTION LAMPS SEALEY

High output lighting with even light spread and low power consumption.

All models feature swivel hook for easy positioning. These main voltage units are manufactured to low voltage directive 73/23/EEC and feature double insulated electrical circuits and BS-approved non-rewirable plug.

8 Watt (290 1132 001 00)

11 Watt (290 1132 002 00)

13 Watt (290 1132 003 00)



Order No. 290 1132 001 00  
 Price £ 18.70  
 Order No. 290 1132 002 00  
 Price £ 26.50  
 Order No. 290 1132 003 00  
 Price £ 29.30  
 incl. freight



**JAGUAR**  
EQUIPMENT PROGRAMME

TEL: 0049-2203-106199 · FAX: 0049-2203-106241

EQS GmbH · Claudiastrasse 2b · 51149 Cologne · Germany



**FREE PHONE****See contact list**

08:00hrs-16:30hrs only.  
Please have details below  
ready when you phone.  
Technical enquiries

**FREE FAX****See contact list**

Please fill out order form below (print  
clearly or type) and fax any time. Fax  
orders can be received 24 hours a day,  
7 days a week.

**Jaguar Equipment  
Programme (JEP)**

EQS GmbH  
Claudiastrasse 2b · 51149 Cologne  
Germany

**Contact List****UK**

TEL: 0800 0856736  
FAX: 0800 0856737

**Austria**

TEL: 00800 291714  
FAX: 00800 291694

**Belgium (Flemish)**

TEL: 00800 36733731  
FAX: 00800 36733292

**Belgium (French)**

TEL: 0800 36733732  
FAX: 0800 36733292

**Denmark**

TEL: 00800 36733732  
FAX: 00800 36733292

**Finland**

TEL: 00800 36733731  
FAX: 00800 36733292

**France**

TEL: 0800 904986  
FAX: 0800 901329

**Germany**

TEL: 0800 3673373  
FAX: 0800 3673329

**Greece**

TEL: 00800 49129046  
FAX: 00800 49129057

**Hungary**

TEL: 00800 36733732  
FAX: 00800 36733292

**Ireland**

TEL: 1800 409574  
FAX: 1800 409580

**Italy**

TEL: 800 790959  
FAX: 800 780959

**Netherlands**

TEL: 00800 36733732  
FAX: 00800 36733292

**Norway**

TEL: 00800 36733732  
FAX: 00800 36733292

**Poland**

TEL: 00800 4911241  
FAX: 00800 4911240

**Portugal**

TEL: 00800 36733732  
FAX: 00800 36733292

**Spain**

TEL: 900 998303  
FAX: 900 998304

**Sweden**

TEL: 00800 36733732  
FAX: 00800 36733292

**Switzerland (French)**

TEL: 00800 36733732  
FAX: 00800 36733292

**Switzerland (German)**

TEL: 00800 36733731  
FAX: 00800 36733291

**All other markets**

TEL: 0049 2203 106199  
FAX: 0049 2203 106241

# Quotation Request Form

Send me an estimate for the following products

Order No.	Description

**I require more information on the following**Wheel and Brake Equipment Lifting Equipment Oil Management System Best Price Guarantee Financing (available only for Great Britain and Spain) Other 

Company stamp

Authorised Repairer: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Phone: \_\_\_\_\_

Fax: \_\_\_\_\_

E-mail: \_\_\_\_\_

07/2004

**Return this form to JEP by Fax or Post.  
Select the Fax number according to your country.**

